



### Upgradeable

19.2kWh to 76.8kWh. Flexible design with each additional unit.



### Live Communications

Real time display, mobile access



### 10 year Warranty

20 year serviceable



### Safe for Home & Environment

Cobalt Free, low voltage  
UL 1642, UL 1973, UN 38.3



## COMMERCIAL SERIES SPECIFICATIONS

Battery Chemistry	LFP
Nominal DC Voltage	48 V DC
Capacity	19.2kWh - 76.8kWh
Max Systems in Parallel	15 (576kWh)
Discharge	13.6kW - 27kW
Charge	13.6kW - 27kW
Communication	Modbus, CAN, or select according to inverter
Warranty	10 year warranty
Service Plan	20 year serviceable
Temp Range	0C - 55C charging, -20C - -55C discharging
Certifications	UN 38.3, UL 1642, UL 1973
Product Dimensions	60 cm x 48 cm x 13.5 cm (23.6 in x 18.9 in x 5.3 in)

### Ordering Options

Casing with 3-Sol-Ark Inverters Pre-Wired (27kW output) and 38.4kWh battery capacity

Casing with 19.2kWh

Casing with 38.4kWh

Casing with 57.6kWh

Casing with 76.8kWh



## PRODUCT DIMENSIONS

